



Tifton GA
 16 Union Industrial Way
 Tifton, GA 31793
 (229) 472-5200

Customer Proposal Letter

Cook County Board of Commissioners
 1200 Hutchinson Avenue
 Adel, GA 31620
 (229) 896-2266

Jeff Lane, thank you for the opportunity to earn your business. We look forward to working with you on your business needs. Please accept the following proposal.

VEHICLE

Make International Model HX620 Year 2022 Stock Number 1314886
 Additional Vehicle and Accessories Description To be delivered on or about 12/31/2021

VIN 3HTPCAPT4NN867401

Quantity	1	Total
Truck Price per Unit	\$160,205.16	\$160,205.16
F.E.T. (Factory & Dealer Paid)	(\$351.38)	(\$351.38)
Net Sales Price	\$159,853.78	\$159,853.78
Optional Extended Warranty(ies)		
State Sales Tax		
Documentary Fee	\$125.00	\$125.00
Administration Fee	\$39.00	\$39.00
Vehicle Inventory Tax		
Additional Taxes		
Tire Recycling Program		
Battery Disposal Fee		
Out of State Vehicle Fee		
Rebate(s)		
Total Sales Price (Including Rebate(s))	\$160,017.78	\$160,017.78
Trade Allowance (see DISCLAIMER Below)		\$0.00

Sales Representative

Daniel Hand

Purchaser

signature

printed name

signature

printed name

Accepted by Sales Manager or
General Manager

title

date

signature

printed name

Quote good until 10/27/2021

Note: The above Customer Proposal is a quotation only. Sale terms subject to approval of Sales Manager of Dealer.

DISCLAIMER: Any order based on this Proposal subject to Customer executing Dealer's standard form Retail Purchase Order incorporating above terms. Any documentary fees, state tax, title, registration and license fees subject to adjustment and change. Actual F.E.T. to be paid by Dealer, subject to adjustment. Any F.E.T. variance will be responsibility of Dealer. Manufacturer has reserved the right to change the price to Dealer of any vehicle not currently in Dealer's stock, without notice to Dealer. If Quoted Vehicle(s) not currently in Dealer's stock, Dealer reserves right to change Quotation Total to reflect any price increases from Manufacturer. This Proposal is based upon Dealer's current and expected inventory, which is subject to change. Dealer not obligated to retain any specific vehicles in stock, nor maintain any specific inventory level. Dealer shall not be obligated to fulfill Proposal in event quoted vehicle(s) not in stock or available within requested delivery schedule at time Proposal accepted. Dealer shall not be liable for any delay in providing or inability to provide Quoted Vehicle(s), where such inability or delay is due, in whole or in part, to any cause beyond the reasonable control of Dealer or is without the gross negligence or intended misconduct of Dealer. Above listed Trade Value based upon current appraisal of Trade Vehicle(s). Dealer may adjust Trade Value of Trade Vehicle(s) to reflect changes in condition and/or mileage of Trade Vehicle(s) between date of current appraisal and acceptance of this Proposal by Customer.

Prepared For:

Cook County Board of Com
 Stacy Griffin
 209 N. Parrish Ave.
 Adel, GA 31620-
 (229)896 - 2266
 Reference ID: N/A

Presented By:

RUSH TRK CTR OF GA
 Brian Hand
 16 UNION INDUSTRIAL WAY
 TIFTON GA 31793 - 8329
 (229)472-5200

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2022 HX620 SBA (HX620)

AXLE CONFIG:	6X4
APPLICATION:	Construction Dump
MISSION:	Requested GVWR: 66000. Calc. GVWR: 60000. Calc. GCWR: 125000 Calc. Start / Grade Ability: 28.51% / 2.46% @ 55 MPH Calc. Geared Speed: 88.4 MPH
DIMENSION:	Wheelbase: 203.00, CA: 134.00, Axle to Frame: 63.00
ENGINE, DIESEL:	{Cummins X15 470 V} Productivity Series, EPA 2021, 470HP @ 1900 RPM, 1750 lb-ft Torque @ 950 RPM, 2000 RPM Governed Speed, 482 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 4500 RDS} 5th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity
AXLE, REAR, TANDEM:	{Meritor MT-40-14X-5DCR-P} Single Reduction, 40,000-lb Capacity, with Lube Oil Pump, .5"(12.7mm) Wall Housing Thickness, Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, R Wheel Ends Gear Ratio: 4.33
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 425/65R22.5 Load Range L XZY-3 (MICHELIN), 465 rev/mile, 65 MPH, All-Position
TIRE, REAR:	(8) 11R24.5 Load Range H HDR2+ (CONTINENTAL), 468 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, TANDEM:	{Hendrickson HMX EX 400} Walking Beam, 40,000-lb Capacity, 54" Axle Spacing, Rubber Springs, with Transverse Torque Rods, Rubber End Bushings
FRAME REINFORCEMENT:	Full Outer C-Channel, Heat Treated Alloy Steel (120,000 PSI Yield), 10.813" x 3.892" x 0.312" (274.6mm x 98.8mm x 7.9mm), 480.0" (12192mm) OAL
PAINT:	Cab schematic 100LZ Location 1: 9219, Winter White (Std) Chassis schematic N/A

Description

Base Chassis, Model HX620 SBA with 203.00 Wheelbase, 134.00 CA, and 63.00 Axle to Frame.

CROSSMEMBER, REAR Relocated to End of Frame

CROSSMEMBER, FRAME TIE for Standard Duty

AXLE CONFIGURATION {Navistar} 6x4

Notes

: Pricing may change if axle configuration is changed.

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 480.0" (12192) Maximum OAL

FRAME REINFORCEMENT Full Outer C-Channel, Heat Treated Alloy Steel (120,000 PSI Yield), 10.813" x 3.892" x 0.312" (274.6mm x 98.8mm x 7.9mm), 480.0" (12192mm) OAL

LICENSE PLATE HOLDER Single Plate, Swing Type, Mounted Below Front Bumper

BUMPER, FRONT Contoured, Aluminum, Stainless Steel Clad, Heavy Duty

TOW PIN, FRONT Heavy Duty; 150,000-lb. Total Capacity

WHEELBASE RANGE 191" (485cm) Through and Including 236" (600cm)

AXLE, FRONT NON-DRIVING {Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity

SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 20,000-lb Capacity, with Shock Absorbers

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

Includes

: BRAKE LINES Color and Size Coded Nylon

: PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel

: PARKING BRAKE VALVE For Truck

: QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4

: SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6

TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck

AIR BRAKE ABS {Bendix AntiLock Brake System} 6-Channel (6 Sensor/6 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control

AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration

AIR COMPRESSOR {Cummins} 18.7 CFM

AIR TANK Polished Aluminum, with Straight Thread O-Ring Ports

AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab

AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Right Rail, Back of Cab, Perpendicular to Rail

AIR COMPRESSOR DISCHARGE LINE 1/2" ID to 5/8" ID Teflon Hose, with Stainless Steel Braid; to Air Dryer

DRAIN VALVE {Bendix DV-2} (2) Automatic, with Heater, for Air Tank

BRAKES, FRONT {Bendix Spicer ADB22X} Air Disc Type, Extended Service, Size 22.5", 23,000-lb Capacity

BRAKES, REAR {Bendix Spicer ADB22X} Air Disc Type, Extended Service, Size 22.5", 26,000-lb Capacity per Axle

BRAKE CHAMBERS, FRONT AXLE 20 SqIn, for Air Disc Brakes

BRAKE CHAMBERS, REAR AXLE 18/24 SqIn Spring Brake, Double Diaphragm, for Air Disc Brakes

PARK BRAKE CHAMBERS, ADDITIONAL (2) Spring Brake Type

Description

STEERING COLUMN Tilting and Telescoping

STEERING WHEEL 4-Spoke; 18" Dia., Black Leather Wrapped

STEERING GEAR (2) {Sheppard M100/M80} Dual Power

DRIVELINE SYSTEM {Dana Spicer} SPL250 Main Driveline with SPL170 Interaxle Shaft, for 6x4

AFTERTREATMENT COVER Polished Aluminum

EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Dual Vertical Tail Pipes, Cab Mounted, Left Side Pipe is Non-Functional/Aesthetic Only

TAIL PIPE (2) Turnback Type, Chrome, 6" Diameter Belled Down to 5" at Muffler

ENGINE COMPRESSION BRAKE {Cummins} Interbrake For Cummins Signature/ISX/X15 Engines; Furnished with Engine

MUFFLER/TAIL PIPE GUARD (2) Bright Stainless Steel

EXHAUST HEIGHT 10'

ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel

: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever

: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light

: STARTER SWITCH Electric, Key Operated

: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector

: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever

: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted

CIGAR LIGHTER Includes Ash Cup

HORN, ELECTRIC (2) Disc Style

ALTERNATOR {Leece-Neville AV1160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount

BODY BUILDER WIRING Rear of Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn

BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud

SPEAKER, AUXILIARY, CB RADIO with Jack for CB; Mounted Left Side Above Driver's Door

BATTERY DISCONNECT SWITCH {Cole-Hersee 75920-06} 300 Amp, Disconnects Cab Power, Does Not Disconnect Charging Circuits, Locks with Padlock, Battery Box Mounted

SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars

CB RADIO Accommodation Package, Header Mounted, Feeds from Accessory Side of Ignition Switch, Includes Power Source, One Antenna and Antenna Base with Wiring on Left Side Mirror

RADIO, AUXILIARY CONTROLS Mounted in Steering Wheel, Radio Function Control Switch, Includes Volume Up/Down, Mute, Forward/Back and Bluetooth Answer/Disconnect

RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input

STOP, TURN, TAIL & B/U LIGHTS {Truck Lite} Super 44, with LED Lights for Stop, Turn and Tail Lights, Truck Lite Super 40 Lamps for Backup Lights, Less Power Module, Includes Incandescent License Plate Light, with Separate Rear Reflectors, Less Rubber Mount

TRAILER CONNECTION SOCKET {Phillips} 7-Way, Mounted at Rear of Frame, Wired for Turn Signals Independent of Stop, Compatible with Trailers with Amber or Side Turn Lamps

BATTERY BOX COVER Polished Aluminum

BATTERY BOX Aluminum, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Right Side Back of Cab

Description

JUMP START STUD Remote Mounted

POWER SOURCE, TERMINAL TYPE 2-Post

TURN SIGNAL SWITCH Self-Canceling

HORN, AIR (2) Rectangular Bell, Chrome

RUNNING LIGHT (2) Daytime

HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on

STARTING MOTOR {Delco Remy 39MT} 12 Volt, Gear Reduced, with Thermal Over-Crank Protection

HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position

ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, with Ignition "OFF" and any Door Opened

CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

POWER SOURCE, ADDITIONAL Auxiliary Power Outlet (APO) & USB Port, Located in the Instrument Panel

HEADLIGHTS Halogen, Composite Combination

SWITCH, MARKER INTERRUPT for Marker Lights and Headlights, Located in Steering Wheel

FENDER EXTENSIONS Rubber

LOGOS EXTERIOR Model Badges

LOGOS EXTERIOR, ENGINE Badges

FRONT END Tilting, Composite

GRILLE Chrome Vertical Accent Bars, with Black Mesh

BUG SCREEN Mounted Behind Grille

PAINT SCHEMATIC, PT-1 Single Color, Design 100

PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

SAFETY TRIANGLES

KEYS - ALL ALIKE, ID I-1624 Compatible with Z-250

CLUTCH Omit Item (Clutch & Control)

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

BLOCK HEATER, ENGINE {Phillips} 120V/1500W

Includes

: BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door

ENGINE, DIESEL {Cummins X15 470 V} Productivity Series, EPA 2021, 470HP @ 1900 RPM, 1750 lb-ft Torque @ 950 RPM, 2000 RPM Governed Speed, 482 Peak HP (Max)

FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed

Includes

: FAN Nylon

AIR CLEANER Dual, Polished Stainless Steel, One Mounted on Each Side of Cowl Ahead of The Doors

ENGINE CONTROL, REMOTE MOUNTED for X15 Engines

EMISSION, CALENDAR YEAR {Cummins X15} EPA, OBD and GHG Certified for Calendar Year 2021

Description

HOSE CLAMPS, RADIATOR HOSES , Mechanical Type; with Constant-Tension Functionality

FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted

RADIATOR DRAIN & FILL FITTING SPECIAL; To Vacuum Out or Fill the Cooling System from the Bottom of Radiator, for Use with Quick-Connect Radiator Drain Tool or Shop Coolant Evacuation-Fill System

CARB IDLE COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal located on Driver Door

RADIATOR Aluminum, Welded, Down Flow, Front to Back System, 1325 SqIn, with 806 SqIn Charge Air Cooler

Includes

: RADIATOR HOSES Premium, Rubber

TRANSMISSION, AUTOMATIC {Allison 4500 RDS} 5th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway

OIL COOLER, AUTO TRANSMISSION {Modine} Remote Mounted; Not for use with Retarder

TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission

SHIFT CONTROL, ELECTRONIC Engine Brake 6th Range Pre-Select for Allison 3000 and 4000 Series Transmission

TRANSMISSION OIL Synthetic; 63 thru 76 Pints

ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS) and Regional Haul Series (RHS), General Purpose Trucks, Construction, Package Number 223

NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released

SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, Performance Programming

PTO CONTROL, DASH MOUNTED For Customer Provided PTO; Includes Switch, Electric/Air Solenoid, Piping and Wiring

AXLE, REAR, TANDEM {Meritor MT-40-14X-5DCR-P} Single Reduction, 40,000-lb Capacity, with Lube Oil Pump, .5"(12.7mm) Wall Housing Thickness, Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, R Wheel Ends . Gear Ratio: 4.33

SUSPENSION, REAR, TANDEM {Hendrickson HMX EX 400} Walking Beam, 40,000-lb Capacity, 54" Axle Spacing, Rubber Springs, with Transverse Torque Rods, Rubber End Bushings

DIFF. SWITCH CONTROLS Two Independent Switches for Control Traction Differentials on Tandem Rear Axles, Mounted on Dash

TRANSVERSE TORQUE RODS {Hendrickson} TRAAX Rod, Transverse Only

DEF TANK COVER Stainless Steel

FUEL/WATER SEPARATOR {Davco Fuel Pro 382} 12 VDC Electric Heater, Includes Pre-Heater, Includes Water-in-Fuel Sensor

FUEL HEATER {Cummins} Plumbing for Thermal Recirculation Valve (TRV) Mounted to Cummins X15 Engines, Thermostatically Controlled

FUEL TANK Polished Aluminum, 24" Dia, 100 US Gal (379L), Mounted Left Side, Under Cab

DEF TANK 10.6 US Gal (40L) Capacity, Frame Mounted Outside Left Rail, Under Cab

CAB Conventional, Day Cab

Includes

: CAB REAR SUSPENSION Air

: CLEARANCE/MARKER LIGHTS (5) LED Roof Mounted

: COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window

: CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area

: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger

: COURTESY LIGHT (2) Driver and Passenger Door Mounted

Description

: DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater Dimming, Center Mounted, Integral to Console
 : FLOOR COVERING Rubber, Black
 : GLASS, ALL WINDOWS Tinted
 : GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side
 : GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side
 : READING LIGHT, CAB Located in Overhead Console
 : STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door

HEATER SHUT-OFF VALVES (1) Ball Valve Type, Supply Line

AIR CONDITIONER with Integral Heater and Defroster

Includes

: HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps

GAUGE CLUSTER Premium Level; English with English Speedometer and Tachometer, for Air Brake Chassis, Includes Engine Coolant Temperature, Primary and Secondary Air Pressure, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 5 Inch LCD Color Display

Includes

: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for

GRAB HANDLE, CAB INTERIOR (2) Safety Yellow

GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster

GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} with Black Bezel, Mounted in Instrument Panel

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

SEAT, DRIVER {ISRI} Series 500, Air Suspension, High Back, Synthetic Leather, Adjustable Bolsters, Double Chamber Lumbar, Heat, Ventilation, Inboard Armrest, Adjustable Shocks, Suspension Cover, Fore/Aft Isolator, Cushion Extension, Seat Tilt, Memory Quickdown

GRAB HANDLE, EXTERIOR (2) Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, for Cab Entry Mounted Left and Right Side at B-Pillar

MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Turn Signals, Bright Heads, Black Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width

Notes

: Mirror Dimensions are Rounded to the Nearest 0.5"

MIRROR, CONVEX, LOOK DOWN Right Side, Bright, 6" x 10.5"

MIRROR, CONVEX, HOOD MOUNTED (2) Right and Left Sides, Bright, 7.5" x 7"

SEAT, PASSENGER {ISRI} Series 500, Air Suspension, High Back, Synthetic Leather, Adjustable Bolsters, Double Chamber Lumbar, Heat, Ventilation, Inboard Armrest, Adjustable Shocks, Suspension Cover, Fore/Aft Isolator, Cushion Extension, Seat Tilt, Memory Quickdown

STORAGE, REAR WALL Storage Pocket, Located on Back Wall Between Driver and Passenger Seats

CAB INTERIOR TRIM Diamond Elite, for Day Cab

Includes

: DOOR TRIM, INTERIOR Bright Handle

: INSTRUMENT PANEL TRIM Black with Woodgrain Accent, Black Gauges with Chrome Bezels

: SUN VISOR (4) Padded Vinyl, 2 Moveable (Front-to-Side) Primary Visors and 2 Flip-down Auxiliary Visors; Vanity Mirrors and Toll Ticket Straps Driver and Passenger Sides

SEAT BELT COMFORT CLIP

HOSE CLAMPS, HEATER HOSE {Breeze} Belleville Washer Type

WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature

Description

FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood

TELEMATICS BRACKET with Universal Mount, 1" Ball Mount Size, Mounted to Plate, Flush Mounted, Upper Left Corner on Front Face of the Wing Panel, Includes (1) APO and (1) USB Port

INSTRUMENT PANEL Wing Panel

MODESTY PANEL Chrome, with Clear Lens LED Lights, for Day Cab

ACCESS, CAB Aluminum, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab or Sleeper Cab

SUNSHADE, EXTERIOR Bright Finish, with Integral Clearance/Marker Lights

CAB SOUND INSULATION Day Cab Interior Noise Reduction Package

WHEELS, FRONT {Accuride 29374} DISC; 22.5x12.25 Rims, Extra Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

WHEELS, REAR {Accuride 42362} DUAL DISC; 24.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Aluminum Hubs

TIRE VALVE CAP Flo-Thru Design

WHEEL BEARING, FRONT, LUBE {EmGard FE-75W-90} Synthetic Oil

(8) TIRE, REAR 11R24.5 Load Range H HDR2+ (CONTINENTAL), 468 rev/mile, 75 MPH, Drive

(2) TIRE, FRONT 425/65R22.5 Load Range L XZY-3 (MICHELIN), 465 rev/mile, 65 MPH, All-Position

Services Section:

WARRANTY Standard for HX520, HX620, Effective with Vehicles Built January 1, 2021 or Later, CTS-2015B