



Tifton GA
16 Union Industrial Way
Tifton, GA 31793
(229) 472-5200

Customer Proposal Letter

Cook County Board of Commissioners
1200 Hutchinson Avenue
Adel, GA 31620
(229) 896-2266

Jeff Lane, thank you for the opportunity to earn your business. We look forward to working with you on your business needs. Please accept the following proposal.

VEHICLE

Make International Model HX620 Year 2022 Stock Number 1314020
Additional Vehicle and Accessories Description To be delivered on or about 12/31/2021

VIN 3HTPCAPT9NN164960
2022 HX Dump Cummins Engine and Allison Transmission

Quantity	1	Total
Truck Price per Unit	\$153,042.44	\$153,042.44
F.E.T. (Factory & Dealer Paid)	(\$276.50)	(\$276.50)
Net Sales Price	\$152,765.94	\$152,765.94
Optional Extended Warranty(ies)		
State Sales Tax		
Documentary Fee	\$125.00	\$125.00
Administration Fee	\$39.00	\$39.00
Vehicle Inventory Tax		
Additional Taxes		
Tire Recycling Program		
Battery Disposal Fee		
Out of State Vehicle Fee		
Rebate(s)		
Total Sales Price (Including Rebate(s))	\$152,929.94	\$152,929.94
Trade Allowance (see DISCLAIMER Below)		\$0.00

Sales Representative

Daniel Hand

Purchaser

signature

printed name

signature

printed name

Accepted by Sales Manager or
General Manager

title

date

signature

printed name

Quote good until 10/27/2021

Note: The above Customer Proposal is a quotation only. Sale terms subject to approval of Sales Manager of Dealer.

DISCLAIMER: Any order based on this Proposal subject to Customer executing Dealer's standard form Retail Purchase Order incorporating above terms. Any documentary fees, state tax, title, registration and license fees subject to adjustment and change. Actual F.E.T. to be paid by Dealer, subject to adjustment. Any F.E.T. variance will be responsibility of Dealer. Manufacturer has reserved the right to change the price to Dealer of any vehicle not currently in Dealer's stock, without notice to Dealer. If Quoted Vehicle(s) not currently in Dealer's stock, Dealer reserves right to change Quotation Total to reflect any price increases from Manufacturer. This Proposal is based upon Dealer's current and expected inventory, which is subject to change. Dealer not obligated to retain any specific vehicles in stock, nor maintain any specific inventory level. Dealer shall not be obligated to fulfill Proposal in event quoted vehicle(s) not in stock or available within requested delivery schedule at time Proposal accepted. Dealer shall not be liable for any delay in providing or inability to provide Quoted Vehicle(s), where such inability or delay is due, in whole or in part, to any cause beyond the reasonable control of Dealer or is without the gross negligence or intended misconduct of Dealer. Above listed Trade Value based upon current appraisal of Trade Vehicle(s). Dealer may adjust Trade Value of Trade Vehicle(s) to reflect changes in condition and/or mileage of Trade Vehicle(s) between date of current appraisal and acceptance of this Proposal by Customer.

Prepared For:

Cook County Board of Com
 Stacy Griffin
 209 N. Parrish Ave.
 Adel, GA 31620-
 (229)896 - 2266
 Reference ID: N/A

Presented By:

RUSH TRK CTR OF GA
 Brian Hand
 16 UNION INDUSTRIAL WAY
 TIFTON GA 31793 - 8329
 (229)472-5200

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile**2022 HX620 SBA (HX620)**

AXLE CONFIG:	6X4
APPLICATION:	Construction Dump
MISSION:	Requested GVWR: 66000. Calc. GVWR: 60000. Calc. GCWR: 125000 Calc. Start / Grade Ability: 21.36% / 2.21% @ 55 MPH Calc. Geared Speed: 87.3 MPH
DIMENSION:	Wheelbase: 207.00, CA: 138.00, Axle to Frame: 77.00
ENGINE, DIESEL:	{Cummins X15 450 V} Productivity Series, EPA 2021, 450HP @ 1900 RPM, 1650 lb-ft Torque @ 950 RPM, 2000 RPM Governed Speed, 461 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 4000 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity
AXLE, REAR, TANDEM:	{Meritor MT-40-14X-4DCR} Single Reduction, 40,000-lb Capacity, .433"(11mm) Wall Housing Thickness, Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, R Wheel Ends Gear Ratio: 4.33
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 425/65R22.5 Load Range L AH32 (HANKOOK), 463 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(8) 11R22.5 Load Range G ENDURANCE RSA (GOODYEAR), 496 rev/mile, 75 MPH, All-Position
SUSPENSION, REAR, TANDEM:	{Hendrickson HMX EX 400} Walking Beam, 40,000-lb Capacity, 54" Axle Spacing, Rubber Springs, with Transverse Torque Rods, Rubber End Bushings
FRAME REINFORCEMENT:	Full Outer C-Channel, Heat Treated Alloy Steel (120,000 PSI Yield), 13.025" x 3.687" x 0.312" (330.8mm x 93.6mm x 7.9mm), 518.0" (13157.2mm) OAL
PAINT:	Cab schematic 100LZ Location 1: 9219, Winter White (Std) Chassis schematic N/A

Description

Base Chassis, Model HX620 SBA with 207.00 Wheelbase, 138.00 CA, and 77.00 Axle to Frame.

CROSSMEMBER, FRAME TIE for Heavy Duty

AXLE CONFIGURATION {Navistar} 6x4

Notes

: Pricing may change if axle configuration is changed.

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 12.250" x 3.380" x 0.375" (304.8mm x 85.6mm x 9.5mm); 550.0" (13970mm) Maximum OAL

FRAME REINFORCEMENT Full Outer C-Channel, Heat Treated Alloy Steel (120,000 PSI Yield), 13.025" x 3.687" x 0.312" (330.8mm x 93.6mm x 7.9mm), 518.0" (13157.2mm) OAL

BUMPER, FRONT Contoured, Aluminum, Stainless Steel Clad, Heavy Duty

TOW PIN, FRONT Heavy Duty; 150,000-lb. Total Capacity

WHEELBASE RANGE 191" (485cm) Through and Including 236" (600cm)

AXLE, FRONT NON-DRIVING {Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity

SUSPENSION, FRONT, SPRING Multileaf, Shackle Type, 20,000-lb Capacity, Less Shock Absorbers

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

Includes

: BRAKE LINES Color and Size Coded Nylon

: PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel

: PARKING BRAKE VALVE For Truck

: QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4

: SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6

AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System

AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration

BRAKE CHAMBERS, FRONT AXLE {Haldex} 24 SqIn

BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake

SLACK ADJUSTERS, FRONT {Haldex} Automatic

SLACK ADJUSTERS, REAR {Haldex} Automatic

AIR COMPRESSOR {Cummins} 18.7 CFM

AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab

AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Right Rail, Back of Cab, Perpendicular to Rail

DUST SHIELDS, FRONT BRAKE for Air Cam Brakes

DUST SHIELDS, REAR BRAKE for Air Cam Brakes

DRAIN VALVE (2) {Berg} with Pull Chains, for Air Tanks

BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle

BRAKES, FRONT {Meritor 16.5X6 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 6", 20,000-lb Capacity

PARK BRAKE CHAMBERS, ADDITIONAL (2) Spring Brake Type

STEERING COLUMN Tilting and Telescoping

Description

STEERING WHEEL 4-Spoke; 18" Dia., Black

STEERING GEAR (2) {Sheppard M100/M80} Dual Power

DRIVELINE SYSTEM {Dana Spicer} SPL250 Main Driveline with SPL170 Interaxle Shaft, for 6x4

AFTERTREATMENT COVER Polished Aluminum

EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Dual Vertical Tail Pipes, Cab Mounted, Left Side Pipe is Non-Functional/Aesthetic Only

ENGINE COMPRESSION BRAKE {Cummins} Interbrake For Cummins Signature/ISX/X15 Engines; Furnished with Engine

TAIL PIPE (2) Turnback Type, Bright

MUFFLER/TAIL PIPE GUARD (2) Bright Stainless Steel

EXHAUST HEIGHT 10'

ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel

: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever

: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light

: STARTER SWITCH Electric, Key Operated

: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector

: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever

: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted

HORN, AIR Single, Located Under Cab

ALTERNATOR {Leece-Neville AV160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount

BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Sleeper, Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn

BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud

SPEAKER, AUXILIARY, CB RADIO with Jack for CB; Mounted Left Side Above Driver's Door

BATTERY DISCONNECT SWITCH {Cole-Hersee 75920-06} 300 Amp, Disconnects Cab Power, Does Not Disconnect Charging Circuits, Locks with Padlock, Battery Box Mounted

SPEAKERS (2) 6.5" Dual Cone Mounted in Doors

CB RADIO Accommodation Package, Header Mounted, Feeds from Accessory Side of Ignition Switch, Includes Power Source, One Antenna and Antenna Base with Wiring on Left Side Mirror

RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input

HORN, ELECTRIC Disc Style

BATTERY BOX Aluminum, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Right Side Back of Cab

POWER SOURCE, TERMINAL TYPE 2-Post

BACK-UP ALARM {Preco 1059} Electronic; Solid State, Dual Function, 112 dBA

TURN SIGNAL SWITCH Self-Canceling

HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position

STARTING MOTOR {Mitsubishi Electric Automotive America 105P} 12-Volt, with Soft-Start

CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

HEADLIGHTS Halogen, Composite Combination

Description

FENDER EXTENSIONS Rubber

LOGOS EXTERIOR Model Badges

LOGOS EXTERIOR, ENGINE Badges

FRONT END Tilting, Composite

GRILLE Chrome Vertical Accent Bars, with Black Mesh

PAINT SCHEMATIC, PT-1 Single Color, Design 100

PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

SAFETY TRIANGLES

CLUTCH Omit Item (Clutch & Control)

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

ENGINE, DIESEL {Cummins X15 450 V} Productivity Series, EPA 2021, 450HP @ 1900 RPM, 1650 lb-ft Torque @ 950 RPM, 2000 RPM Governed Speed, 461 Peak HP (Max)

FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed

Includes

: FAN Nylon

AIR CLEANER Dual, Polished Stainless Steel, One Mounted on Each Side of Cowl Ahead of The Doors

EMISSION, CALENDAR YEAR {Cummins X15} EPA, OBD and GHG Certified for Calendar Year 2021

HOSE CLAMPS, RADIATOR HOSES {Gates} Shrink Band Type

FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted

RADIATOR DRAIN & FILL FITTING SPECIAL; To Vacuum Out or Fill the Cooling System from the Bottom of Radiator, for Use with Quick-Connect Radiator Drain Tool or Shop Coolant Evacuation-Fill System

CARB IDLE COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood

RADIATOR Aluminum, Welded, Down Flow, Front to Back System, 1325 SqIn, with 806 SqIn Charge Air Cooler

Includes

: RADIATOR HOSES Premium, Rubber

TRANSMISSION, AUTOMATIC {Allison 4000 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway

OIL COOLER, AUTO TRANSMISSION {Modine} Remote Mounted; Not for use with Retarder

TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission

TRANSMISSION OIL Synthetic; 63 thru 76 Pints

ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS) and Regional Haul Series (RHS), General Purpose Trucks, Construction, Package Number 223

NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released

SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, Performance Programming

PDL WARNING BUZZER Power Divider Lock

AXLE, REAR, TANDEM {Meritor MT-40-14X-4DCR} Single Reduction, 40,000-lb Capacity, .433"(11mm) Wall Housing Thickness, Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, R Wheel Ends . Gear Ratio: 4.33

Description

SUSPENSION, REAR, TANDEM {Hendrickson HMX EX 400} Walking Beam, 40,000-lb Capacity, 54" Axle Spacing, Rubber Springs, with Transverse Torque Rods, Rubber End Bushings

DIFF. SWITCH CONTROLS Two Independent Switches for Control Traction Differentials on Tandem Rear Axles, Mounted on Dash

TRANSVERSE TORQUE RODS {Hendrickson} TRAAX Rod, Transverse Only

FUEL/WATER SEPARATOR {Racor} Fuel Pre-Filter and Filter Base, Includes Water-In-Fuel Sensor

FUEL HEATER {Cummins} Omit Plumbing for TRV on Cummins Engines

FUEL TANK Polished Aluminum, 24" Dia, 100 US Gal (379L), Mounted Left Side, Under Cab

DEF TANK 10.6 US Gal (40L) Capacity, Frame Mounted Outside Left Rail, Under Cab

CAB Conventional, Day Cab

Includes

- : CAB REAR SUSPENSION Air
- : CLEARANCE/MARKER LIGHTS (5) LED Roof Mounted
- : COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window
- : CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area
- : CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger
- : COURTESY LIGHT (2) Driver and Passenger Door Mounted
- : DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater Dimming, Center Mounted, Integral to Console
- : FLOOR COVERING Rubber, Black
- : GLASS, ALL WINDOWS Tinted
- : GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side
- : GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side
- : READING LIGHT, CAB Located in Overhead Console
- : STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door

AIR CONDITIONER with Integral Heater and Defroster

Includes

- : HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps

GAUGE CLUSTER Premium Level; English with English Speedometer and Tachometer, for Air Brake Chassis, Includes Engine Coolant Temperature, Primary and Secondary Air Pressure, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 5 Inch LCD Color Display

Includes

- : GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for

GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} with Black Bezel, Mounted in Instrument Panel

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

SEAT, DRIVER {ISRI} Series 500, Air Suspension, High Back, Synthetic Leather, Adjustable Bolsters, Double Chamber Lumbar, Heat, Ventilation, Inboard Armrest, Adjustable Shocks, Suspension Cover, Fore/Aft Isolator, Cushion Extension, Seat Tilt, Memory Quickdown

GRAB HANDLE, EXTERIOR (2) Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, for Cab Entry Mounted Left and Right Side at B-Pillar

MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Bright Heads, Black Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width

Notes

- : Mirror Dimensions are Rounded to the Nearest 0.5"

MIRROR, CONVEX, HOOD MOUNTED (2) Right and Left Sides, Black, 7.5" x 7"

Description

SEAT, PASSENGER {ISRI} Series 500, Air Suspension, High Back, Synthetic Leather, Adjustable Bolsters, Double Chamber Lumbar, Heat, Ventilation, Inboard Armrest, Adjustable Shocks, Suspension Cover, Fore/Aft Isolator, Cushion Extension, Seat Tilt, Memory Quickdown

SEAT BELT All Red; 1 to 3

CAB INTERIOR TRIM Diamond Elite, for Day Cab

Includes

: DOOR TRIM, INTERIOR Bright Handle

: INSTRUMENT PANEL TRIM Black with Woodgrain Accent, Black Gauges with Chrome Bezels

: SUN VISOR (4) Padded Vinyl, 2 Moveable (Front-to-Side) Primary Visors and 2 Flip-down Auxiliary Visors; Vanity Mirrors and Toll Ticket Straps Driver and Passenger Sides

WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature

WINDOW, REAR Polycarbonate Plastic Window, Shatter Resistant

INSTRUMENT PANEL Wing Panel

MODESTY PANEL Painted

ACCESS, CAB Aluminum, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab or Sleeper Cab

WHEELS, FRONT {Accuride 29374} DISC; 22.5x12.25 Rims, Extra Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

WHEELS, REAR {Accuride 42644} DUAL DISC; 22.5x8.25 Rims, Extra Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

(8) TIRE, REAR 11R22.5 Load Range G ENDURANCE RSA (GOODYEAR), 496 rev/mile, 75 MPH, All-Position

(2) TIRE, FRONT 425/65R22.5 Load Range L AH32 (HANKOOK), 463 rev/mile, 75 MPH, All-Position

Services Section:

WARRANTY Standard for HX520, HX620, Effective with Vehicles Built January 1, 2021 or Later, CTS-2015B